

Synthes 3.7 mm Cannulated Locking and Conical Screw Set (01.240.016)

Instruments and Storage

Catalog #	Description
319.35	1.6 mm Cleaning Stylet
360.266	1.6 mm Wire Guide (2)
900.601	1.6 mm Drill Tip Guide Wire, 150 mm (3)
03.240.001	Direct Measuring Device
314.114	Cannulated StarDrive Screwdriver
310.65	3.2 mm Cannulated Drill Bit, Quick Coupling, 170 mm
03.240.002	Cannulated StarDrive Screwdriver Shaft, T15, Quick Coupling, 150 mm
60.240.016	Graphic Case, Complete, for 3.7 mm Cannulated Locking and Conical Screws (including 2 screw racks and instrument tray)

3.7 mm Cannulated Conical Screws, Partially Threaded, Stainless Steel

Catalog #	Description
02.240.210	10 mm
02.240.212	12 mm (2)
02.240.214	14 mm (2)
02.240.216	16 mm (2)
02.240.218	18 mm (2)
02.240.220	20 mm (2)
02.240.222	22 mm (2)
02.240.224	24 mm (2)
02.240.226	26 mm (2)
02.240.228	28 mm
02.240.230	30 mm (2)
02.240.232	32 mm (2)
02.240.234	34 mm (2)
02.240.236	36 mm (2)
02.240.238	38 mm (2)
02.240.240	40 mm (2)
02.240.242	42 mm (4)
02.240.244	44 mm (4)
02.240.246	46 mm (4)
02.240.248	48 mm (4)
02.240.250	50 mm (4)
02.240.252	52 mm (4)
02.240.254	54 mm (4)
02.240.256	56 mm (4)
02.240.258	58 mm (4)
02.240.260	60 mm (4)
02.240.265	65 mm (2)
02.240.270	70 mm (2)
02.240.275	75 mm (2)
02.240.280	80 mm (2)
02.240.285	85 mm (2)
02.240.290	90 mm (2)
02.240.295	95 mm (2)

3.7 mm Cannulated Locking Screws, Fully Threaded, Stainless Steel

Catalog #	Description
02.240.010	10 mm
02.240.014	14 mm
02.240.016	16 mm (2)
02.240.018	18 mm (2)
02.240.020	20 mm (2)
02.240.022	22 mm (2)
02.240.024	24 mm (2)
02.240.026	26 mm (2)
02.240.028	28 mm (2)
02.240.030	30 mm (2)
02.240.032	32 mm (2)
02.240.034	34 mm (2)
02.240.036	36 mm (2)
02.240.038	38 mm (2)
02.240.040	40 mm (2)
02.240.042	42 mm (4)
02.240.044	44 mm (4)
02.240.046	46 mm (4)
02.240.048	48 mm (4)
02.240.050	50 mm (4)
02.240.052	52 mm (4)
02.240.054	54 mm (4)
02.240.056	56 mm (4)
02.240.058	58 mm (4)
02.240.060	60 mm (4)
02.240.065	65 mm
02.240.070	70 mm (2)
02.240.075	75 mm (2)
02.240.080	80 mm (2)
02.240.085	85 mm (2)
02.240.090	90 mm (2)
02.240.095	95 mm (2)